



FILTRATION & FERTIGATION
GRAVEL FILTERS

FILTRATION & FERTIGATION

GRAVEL FILTERS



SINGLE METAL GRAVEL FILTER WITH BACKFLUSH

Body material: S195T
Max working pressure: 8 bar
Max working temperature: 60 °C

Product code	Size	Dimensions	Flow
063 G1F 020 600 000	2"	Ø600 mm	20 m ³ /h
075 G1F 025 600 000	2 ½"	Ø600 mm	25 m ³ /h
090 G1F 035 660 000	3"	Ø660 mm	35 m ³ /h
110 G1F 050 660 000	4"	Ø660 mm	50 m ³ /h



DOUBLE METAL GRAVEL FILTER WITH BACKFLUSH

Body material: S195T
Max working pressure: 8 bar
Max working temperature: 60 °C

090 G2F 050 660 000	3"	Ø660 mm	50 m ³ /h
110 G2F 070 660 000	4"	Ø660 mm	70 m ³ /h



TRIPLE METAL GRAVEL FILTER WITH BACKFLUSH

Body material: S195T
Max working pressure: 8 bar
Max working temperature: 60 °C

140 G3F 100 660 000	5"	Ø660 mm	100 m ³ /h
---------------------	----	---------	-----------------------



QUADRUPLE METAL GRAVEL FILTER WITH BACKFLUSH

Body material: S195T
Max working pressure: 8 bar
Max working temperature: 60 °C

160 G4F 140 660 000	6"	Ø660 mm	140 m ³ /h
---------------------	----	---------	-----------------------



HEADQUARTERS

Orhan Gazi Mah. Isiso San. Sit.
15. Yol Y Blok No: 33 34538
Esenyurt, İstanbul, Turkey
+90 212 623 23 08

FACTORY

Organize Sanayi Bölgesi Bursa
Karayolu 6. km. 2. Cd. No: 2
Çanakkale, Turkey
+90 286 214 32 07

Website www.sunstream.com.tr | **Support** info@sunstream.com.tr

© 2022 İSKO Plastik ve Kalıp San. Tic. A.Ş.