



**DRIP IRRIGATION FITTINGS**  
**OFFTAKE CONNECTORS**

# DRIP IRRIGATION FITTINGS

## OFFTAKE CONNECTORS



### OFFTAKE CONNECTOR WITH RING

Connects thin wall dripline to sealing rubber inserted outlet

Product code	Size	Bag quantity	Box quantity	Box weight
016 OFY C14 000 Y16	14 x 16 mm	50	1000	7,1 kg
016 OFY C16 000 Y16	16 x 16 mm	50	1000	7,3 kg
020 OFY C20 000 Y20	20 x 20 mm	50	700	6,6 kg
022 OFY C20 000 Y22	20 x 22 mm	50	400	5,4 kg
025 OFY C25 000 Y25	25 x 25 mm	50	350	5,6 kg



### OFFTAKE CONNECTOR WITH NUT

Connects thin/medium wall dripline to sealing rubber inserted outlet

016 OFS C14 000 S16	14 x 16 mm	50	700	7,5 kg
016 OFS C16 000 S16	16 x 16 mm	50	600	6,2 kg
020 OFS C16 000 S20	16 x 20 mm	50	400	4,9 kg
020 OFS C20 000 S20	20 x 20 mm	50	400	4,9 kg
022 OFS C20 000 S22	20 x 22 mm	50	350	5,1 kg
025 OFS C25 000 S25	25 x 25 mm	50	200	4,6 kg



### BARBED OFFTAKE CONNECTOR

Connects thick wall dripline to sealing rubber inserted outlet

016 OFK C15 000 K16	15 x 16 mm	50	1200	5,5 kg
016 OFK C16 000 K16	16 x 16 mm	50	1200	5,2 kg
020 OFK C20 000 K20	20 x 20 mm	50	750	4,4 kg
025 OFK C25 000 K25	25 x 25 mm	50	400	4,2 kg



### SELF-SEAL BARBED OFFTAKE CONNECTOR

Connects thick wall dripline to outlet w/o sealing rubber

016 OCK C16 D17 K16	16 x 16 mm	50	1100	6,6 kg
---------------------	------------	----	------	--------



### MALE THREADED OFFTAKE CONNECTOR

Obtains male thread from sealing rubber inserted outlet

020 OFM C20 000 M04	20 mm x 3/4"	50	500	5,9 kg
---------------------	--------------	----	-----	--------



### LOCK TYPE OFFTAKE CONNECTOR

Connects medium/thick wall dripline to sealing rubber inserted outlet

016 OFG C20 000 G16	20 x 16 mm	50	300	7,8 kg
020 OFG C20 000 G20	20 x 20 mm	50	300	7,8 kg

## DRIP IRRIGATION FITTINGS OFFTAKE CONNECTORS



### MALE THREADED OFFTAKE CONNECTOR WITH RING

Connects thin wall  
dripline to female  
threaded outlet

Product code	Size	Bag quantity	Box quantity	Box weight
016 OFY M03 000 Y16	16 mm x 1/2"	50	700	7,1 kg
016 OFY M04 000 Y16	16 mm x 3/4"	50	500	6,8 kg
020 OFY M04 000 Y20	20 mm x 3/4"	50	400	5,9 kg
022 OFY M04 000 Y22	22 mm x 3/4"	50	400	6,3 kg



### MALE THREADED OFFTAKE CONNECTOR WITH NUT

Connects thin/medium  
wall dripline to female  
threaded outlet

016 OFS M03 000 S16	16 mm x 1/2"	50	600	7,3 kg
016 OFS M04 000 S16	16 mm x 3/4"	50	450	7,3 kg
020 OFS M04 000 S20	20 mm x 3/4"	50	350	5,9 kg
022 OFS M04 000 S22	22 mm x 3/4"	50	350	5,6 kg



### MALE THREADED LOCK TYPE OFFTAKE CONNECTOR

Connects medium/thick  
wall dripline to female  
threaded outlet

016 OMG M03 000 G16	16 mm x 1/2"	50	400	8 kg
016 OMG M04 000 G16	16 mm x 3/4"	50	300	8,1 kg
020 OMG M04 000 G20	20 mm x 3/4"	50	300	8,1 kg



### FEMALE THREADED OFFTAKE CONNECTOR WITH RING

Connects thin wall  
dripline to male threaded  
outlet

016 OFY F03 000 Y16	16 mm x 1/2"	50	700	7,4 kg
---------------------	--------------	----	-----	--------



### FEMALE THREADED OFFTAKE CONNECTOR WITH NUT

Connects thin/medium  
wall dripline to male  
threaded outlet

016 OFS F03 000 S16	16 mm x 1/2"	50	600	7,3 kg
---------------------	--------------	----	-----	--------



### COMPRESSION OFFTAKE CONNECTOR WITH NUT

Connects thin/medium  
wall dripline to outlet  
w/o sealing rubber

016 OFS D08 N06 S16	8 x 16 mm	50	600	8,4 kg
---------------------	-----------	----	-----	--------



### LAY FLAY SPIRAL OFFTAKE CONNECTOR WITH RING

Connects thin wall  
dripline to lay flat main  
pipe

016 OFL P16 000 Y16	16 x 16 mm	50	450	6,9 kg
---------------------	------------	----	-----	--------

# DRIP IRRIGATION FITTINGS

## OFFTAKE CONNECTORS



### LAY FLAY SPIRAL OFFTAKE CONNECTOR WITH NUT

Connects thin/medium wall dripline to lay flat main pipe

Product code	Size	Bag quantity	Box quantity	Box weight
016 OFL P16 000 S16	16 x 16 mm	50	300	5,4 kg



### LAY FLAT OFFTAKE CONNECTOR WITH MALE NUT

Obtains male thread from lay flat main pipe

013 OFX P13 000 M04	13 mm x 3/4"	50	450	6,2 kg
018 OFX P18 000 M04	18 mm x 3/4"	50	450	6,2 kg



### LAY FLAT SPIRAL OFFTAKE CONNECTOR WITH MALE NUT

Obtains male thread from lay flat main pipe

016 OFU P16 000 M04	16 mm x 3/4"	50	450	5,9 kg
---------------------	--------------	----	-----	--------



### LAY FLAT OFFTAKE CONNECTOR WITH FEMALE NUT

Obtains female thread from lay flat main pipe

013 OFX P13 000 F03	13 mm x 1/2"	50	400	6,6 kg
013 OFX P13 000 F04	13 mm x 3/4"	50	350	7,2 kg
018 OFX P18 000 F03	18 mm x 1/2"	50	400	6,6 kg
018 OFX P18 000 F04	18 mm x 3/4"	50	350	7,2 kg



### LAY FLAT SPIRAL OFFTAKE CONNECTOR WITH FEMALE NUT

Obtains female thread from lay flat main pipe

016 OFU P16 000 F03	16 mm x 1/2"	50	400	6,3 kg
016 OFU P16 000 F04	16 mm x 3/4"	50	350	6,9 kg



### LAY FLAT OFFTAKE MALE NUT

Obtains male thread from lay flat main pipe when connected with offtake bolt

012 ALS F03 000 M04	1/2" x 3/4"	50	600	5,3 kg
---------------------	-------------	----	-----	--------



### LAY FLAT OFFTAKE FEMALE NUT

Obtains female thread from lay flat main pipe when connected with offtake bolt

012 ALS F03 000 F03	1/2" x 1/2"	50	600	6,9 kg
012 ALS F03 000 F04	1/2" x 3/4"	50	450	6,8 kg

## DRIP IRRIGATION FITTINGS OFFTAKE CONNECTORS



### LAY FLAT OFFTAKE BOLT

Obtains male/female thread from lay flat main pipe when connected with offtake nut

Product code	Size	Bag quantity	Box quantity	Box weight
013 X13 P13 000 M03	13 mm x 1/2"	50	1500	7 kg
018 X18 P18 000 M03	18 mm x 1/2"	50	1500	6,9 kg



### LAY FLAT SPIRAL OFFTAKE BOLT

Obtains male/female thread from lay flat main pipe when connected with offtake nut

016 U16 P16 000 M03	16 mm x 1/2"	50	1500	6 kg
---------------------	--------------	----	------	------



**HEADQUARTERS**

Orhan Gazi Mah. Isiso San. Sit.  
15. Yol Y Blok No: 33 34538  
Esenyurt, İstanbul, Turkey  
+90 212 623 23 08

**FACTORY**

Organize Sanayi Bölgesi Bursa  
Karayolu 6. km. 2. Cd. No: 2  
Çanakkale, Turkey  
+90 286 214 32 07

**Website** [www.sunstream.com.tr](http://www.sunstream.com.tr) | **Support** [info@sunstream.com.tr](mailto:info@sunstream.com.tr)

© 2022 İSKO Plastik ve Kalıp San. Tic. A.Ş.